

Printing date 30.10.2009 Revision: 30.10.2009

1 Identification of the substance/preparation and of the company/undertaking

· Product details

· Trade name: PP-Primer

· Article number: Series 10-PP

- · Application of the substance / the preparation Cleaning material/ Detergent
- · Manufacturer/Supplier:

Printcolor Screen Ltd.

DECO TECHnology Group Inc.

Tel: (714) 639-3326 Fax: (714) 639-2261

- · Further information obtainable from: Product safety department
- · Information in case of emergency: Tel: (800) 535-5053

2 Hazards identification

· Hazard description:



Xn Harmful

· Information concerning particular hazards for human and environment:

R 10 Flammable.

R 20/21 Harmful by inhalation and in contact with skin.

R 38 Irritating to skin.

3 Composition/information on ingredients

- · Chemical characterization:
- · CAS No. Description
- 1330-20-7 xylene
- Identification number(s) EINECS Number: 215-535-7
- · Index number: 601-022-00-9

4 First aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

5 Fire-fighting measures

- · Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet

(Contd. on page 2)



Printing date 30.10.2009 Revision: 30.10.2009

Trade name: PP-Primer

(Contd. of page 1)

Protective equipment:

Mouth respiratory protective device.

Wear self-contained respiratory protective device.

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

7 Handling and storage

- · Handling:
- Information for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene (50-100%)

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

- Additional information: The lists valid during the making were used as basis.
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:





Printing date 30.10.2009 Revision: 30.10.2009

Trade name: PP-Primer

(Contd. of page 2)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber, BR

Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information	
Form: Colour: Odour:	Fluid Colourless Characteristic
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	
· Flash point:	30°C (Abel Pensky)
· Ignition temperature:	500°C
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	7 Vol %
· Vapour pressure at 20°C:	6.7-8.2 hPa
· Density at 20°C:	0.87 g/cm³
· Solubility in / Miscibility with water at 20°C:	0.2 g/l
· Viscosity: Dynamic at 20°C: VOC (EC)	5 mPas 98.70 %

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Dangerous reactions No dangerous reactions known.

(Contd. on page 4)



Printing date 30.10.2009 Revision: 30.10.2009

Trade name: PP-Primer

(Contd. of page 3)

· Dangerous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Acute toxicity:
- · LD/LC50 values relevant for classification:

1330-20-7 xylene

Oral LD50 4300 mg/kg (rat)
Dermal LD50 2000 mg/kg (rabbit)

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

12 Ecological information

· General notes:

Water hazard class 2 (German Regulation) (Assessment by list): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

13 Disposal considerations

- · Product:
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · European waste catalogue 07 07 04: other organic solvents, washing liquids and mother liquors
- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

· Land transport ADR/RID (cross-border)



· **ADR/RID class:** 3 Flammable liquids.

Danger code (Kemler): 30
UN-Number: 1210
Packaging group: |||
Hazard label: 3

· Description of goods: 1210 PRINTING INK RELATED MATERIAL

· Maritime transport IMDG:



• **IMDG Class:** 3 • **UN Number:** 1210

(Contd. on page 5)



Printing date 30.10.2009 Revision: 30.10.2009

Trade name: PP-Primer

(Contd. of page 4)

· Label 3 · Packaging group: III · EMS Number: F-E,S-D · Marine pollutant: No

Proper shipping name: PRINTING INK RELATED MATERIAL

· Air transport ICAO-TI and IATA-DGR:



· ICAO/IATA Class: 3 · UN/ID Number: 1210 · Label 3 · Packaging group: |||

· Proper shipping name: PRINTING INK RELATED MATERIAL

15 Regulatory information

· Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:



Xn Harmful

· Risk phrases:

10 Flammable.

20/21 Harmful by inhalation and in contact with skin.

38 Irritating to skin.

Safety phrases:

- 9 Keep container in a well-ventilated place.
- 23 Do not breathe fumes/aerosol.
- 25 Avoid contact with eyes.
- 36/37 Wear suitable protective clothing and gloves.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 60 This material and its container must be disposed of as hazardous waste.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing MSDS: Product safety department
- · Contact:

Richard Gähwiler

richard.gaehwiler@printcolor.ch