

# SAFETY DATA SHEET

NOTICE: Judgment may be based on indirect test and technical literature. The OSHA Hazard Communication Standard only requires SDS's and special labeling for materials defined as "HAZARDOUS"; see 29 CFR 1910.1200 (c). This document may be about a product which is NOT hazardous but is provided as information for our customers. See references for information.

## SECTION 1. IDENTIFICATION

Product Identifier: NS-114	Emergency Telephone #: (800) 535-5053
Product Use: Neo-Solv	General Information #: (714) 639-3326
Manufactured by: Deco Technology Group, Inc. 1040 Segovia Cir Placentia, CA 92870	Date Prepared: August 10, 2015

## SECTION 2. HAZARD(S) IDENTIFICATION

GHS Hazard Codification:



Signal Word: WARNING

Hazard Class	Category	Code	Hazard Statement
Flammable Liquid	3	H226	Flammable liquid and vapor
Aspiration Hazard	1	H304	May be fatal if swallowed and enters airways
Skin Irritation	2	H315	Causes skin irritation
Serious Eye Irritation	2A	H319	Causes serious eye irritation
STOT, Single Exposure; Narcotic effects	3	H336	May cause drowsiness or dizziness
Hazardous to the Aquatic Environment, Long-term hazard	2	H411	Toxic to aquatic life with long-lasting effects

Precautionary	Code	Statement
Prevention	P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing fumes/mists/ vapors/sprays. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
	P233	
	P240	
	P241	
	P242	
	P243	
	P261	
	P264	
	P271	
	P273	
Response	P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting. IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water/shower. IF ON SKIN: Wash with soap and water. Specific treatments: See Section 4 First Aid Measures. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. In case of fire: Use foam, dry chemical, carbon dioxide fire extinguishers or water spray for extinction. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if easy to do so. Continue rinsing. If eye irritation persists: Get medical advice/attention. Collect spillage.
	P331	
	P303+P361+P353	
	P302 + P352	
	P321	
	P332+P313	
	P362	
	P370+P378	
	P304+P340	
	P312	
Storage	P305+P351+P338	Store in a well ventilated place. Keep container tightly closed. Keep cool. Store locked up.
	P337+P313	
Disposal	P391	Dispose of contents/container in compliance with all Federal, State/Provincial and local laws and regulations.

Description of any hazards not otherwise classified: May cause eye irritation. May cause skin defatting (dermatitis). May be harmful if absorbed through the skin. Inhalation of mists/vapors/sprays may cause irritation of respiratory tract. May be harmful if inhaled. May be harmful if swallowed. Forms peroxides of unknown stability. Vapors may form explosive mixture with air.

## SECTION 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Common Name	CAS #	Concentration Range %
Dibasic Ester	DBE	Mixture	46 – 50
Naphtha (petroleum), heavy alkylate	OMS	64741-65-7	20 – 24
2-(2-butoxyethoxy)ethanol	DB	112-34-5	11 – 15
D-Limonene	Orange Terpenes	5989-27-5	8 – 12

## SECTION 4. FIRST AID MEASURES

Eyes: Flush well with water for at least 15 minutes, holding eyelids open. Remove any contact lenses and continue rinsing. Seek medical attention if irritation persists.

**Skin:** Remove immediately all contaminated clothing and launder before reuse. Rinse skin with water/shower. Wash with soap and water. If irritation persists, seek medical attention.

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing – Call a POISON CENTER or doctor/physician if you feel unwell. If breathing is difficult, have a trained person administer oxygen. If respiration stops, have a trained person administer artificial respiration by way of pocket mask equipped with one-way valve or other proper respiratory device – Do NOT use mouth-to-mouth method if victim inhaled material. Call a physician.

**Ingestion:** Immediately call a POISON CENTER or doctor/physician. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep head below hips to prevent aspiration.

#### SECTION 5. FIRE-FIGHTING MEASURES

**Flammability:** Class II Combustible Liquid

**Flash Point:** 124°F (51°C)

**Extinguishing Media:** Foam, dry chemical, carbon dioxide fire extinguishers. Do not spray water directly on fire. Use water spray to cool containers.

**Specific hazards arising from chemical:** Vapors are heavier than air and may travel along the ground to an ignition source. Readily ignited by static discharge. Do not allow run-off from fire fighting to enter drains or water courses.

**Hazardous combustion products:** Carbon monoxide and carbon dioxide.

**Firefighting protective equipment:** Wear a self-contained breathing apparatus with a full face piece operated in the positive pressure demand mode with appropriate turn-out gear and chemical resistant personal protective equipment.

**Sensitivity to static discharge:** This product is combustible and readily ignited even by static discharge. Grounding equipment is recommended.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

**Personal Precautions:** Use personal protective equipment (Section 8). Eliminate all sources of ignition – No smoking. Ventilate area. Avoid breathing fumes/mists/ vapors/sprays. Avoid release to the environment – Collect spillage. Wash thoroughly after handling.

**For Small Spills:** Spilled material may be slippery. Avoid dispersal of material and runoff into soil, waterways, drains and sewers. Vapor-suppressing foam may be used to reduce vapors. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste with non-sparking tools. Wash walking surfaces with water to reduce slipping hazard. Dispose of contaminated absorbent material in accordance with local, state and federal regulations.

**For Large Spills:** Large spills cannot occur due to packaging.

#### SECTION 7. HANDLING AND STORAGE

**Handling:** Wear personal protection equipment (Section 8). Use only outdoors or in a well-ventilated area. Avoid breathing fumes/mists/vapors/sprays. Do not handle around sources of ignition. Use proper bonding and grounding during product transfer as described in document NFPA 77. Use explosion-proof equipment and non-sparking tools. Take precautionary measures against static discharge. Vapors are heavier than air and may travel along the ground to an ignition source. Never use welding or cutting torch on or near drum (even empty) because product can ignite explosively. Do not premix with other chemicals. Avoid release to the environment – Collect spillage. Do not eat, drink or smoke in work areas. Wash thoroughly after handling.

**Storage:** Keep away from heat, flame, or sunlight – keep cool. Keep from freezing. Keep container tightly closed when not in use. Store locked up. Store in a well-ventilated place. Protect from physical damage. Store away from strong oxidizing agents, acids, bases and reducing agents.

#### SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Ingredient	CAS #	OSHA/PEL	ACGIH/TLV	STEL
Dibasic Ester	Mixture	1.5 ppm	Not established	Not established
Naphtha (petroleum), heavy alkylate	64741-65-7	500 ppm	Not established	Not established
2-(2-butoxyethoxy)ethanol	112-34-5	Not established	10 ppm	Not established
D-Limonene	5989-27-5	Not established	30 ppm	30 ppm

**Engineering Controls:** Provide adequate ventilation. Observe occupational exposure limits and keep the risk of exposure to a minimum.

**Personal protective equipment:**

**Eye:** Safety glasses with side shields or splash proof goggles.

**Skin:** Chemical resistant (impervious) gloves. Normal materials handling clothing.

**Respirator:** Use NIOSH approved protection if PEL is exceeded or if vapors are causing irritation.

**Other:** Use only in a well ventilated area. Do not eat, drink or smoke while handling. Wash thoroughly after handling.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	Light straw, clear liquid	Upper/Lower flammability limits	Not determined
Odor	Cherry	Vapor pressure	>0.1mmHg @ 20°C
Odor threshold	Not determined	Vapor density (Air = 1)	>1
pH	Not applicable	Specific gravity (water = 1.0)	0.950 g/ml
Melting point	Not determined	Solubility	Insoluble in water
Freezing point	Not determined	Partition coefficient (n-octanol/water)	Not determined
Boiling point	Not determined	Auto-ignition temperature	Not determined
Flash point	124°F (51°C)	Decomposition temperature	Not determined
Evaporation rate (n-butyl acetate=1)	<1	Viscosity	Not determined
Flammability	Class II Combustible	%Volatile/Volume	93

#### SECTION 10. STABILITY AND REACTIVITY

**Reactivity:** 2-(2-butoxyethoxy)ethanol vapors may form explosive mixture with air. 2-(2-butoxyethoxy)ethanol - forms peroxides of unknown stability.

Chemical stability: Stable under normal, ambient temperature and conditions.  
Possibility of hazardous reactions: Hazardous polymerization will not occur.  
Conditions to avoid: Heat, flame and sparks. Keep from freezing. Do not mix with other chemicals  
Incompatible materials: Avoid strong oxidizing agents, acids, bases and reducing agents.  
Hazardous combustion products: Carbon monoxide and carbon dioxide.

#### SECTION 11. TOXICOLOGICAL INFORMATION

---

Acute and Chronic Toxicity (short and long term):

Oral (LD50 Rat): >2000 mg/kg  
Dermal (LD50 Rabbit): Not determined  
Inhalation (LC50 Rat): >200 ppm 2-(2-butoxyethoxy)ethanol

Eye Contact: Serious eye irritant.

Skin Contact: Skin irritant. May cause skin defatting (dermatitis). May be harmful if absorbed through the skin.

Inhalation: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Inhalation of mists/vapors/sprays may cause irritation of respiratory tract. May be harmful if inhaled.

Ingestion: May irritate the mouth, throat and gastrointestinal tract. May be fatal if swallowed and enters airways. May be harmful if swallowed.

NTP/IARC/OSHA Carcinogen: IARC Group 2B – Naphtha (petroleum), heavy alkylate CAS #64741-65-7, IARC Group 3 – Orange Terpenes CAS# 5989-27-5

#### SECTION 12. ECOLOGICAL INFORMATION

---

Aquatic Effects:

96h LC-50 (fish): Not determined  
96h EC-50 (invertebrates): Not determined  
48h LC-50 (algae): Not determined

Persistence and degradability: Not determined

Bioaccumulation: Not determined

Mobility: This product floats on water. This product is volatile and may spread in the atmosphere. Soil mobility not determined.

Effects on Aquatic Life: Hazardous to the Aquatic Environment, Long-term hazard Category 2: Avoid release to the environment – Collect spillage.

#### SECTION 13. DISPOSAL CONSIDERATIONS

---

Disposal of Wastes: Do not dump into sewers, on the ground or into any waterways. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations.

Contaminated Packaging: Since emptied containers retain product residue, follow label warnings even after container is emptied. Do not cut, drill, grind or weld on or near the container.

RCRA: A waste containing this product may have the RCRA hazardous waste no. D001 (Ignitable) (40 CFR 261.22).

#### SECTION 14. TRANSPORT INFORMATION

---

United States DOT

Container of 119 gallons or less:

Combustible Liquid (49 CFR 173.120(b)(2): This material is not regulated under 49 CFR if in a container of 119 gallon capacity or less for ground transportation. Exception CFR 173.150(f)(2): Combustible liquids. This exception does not apply to transportation by vessel or aircraft.

Container of 120 gallons or more:

UN/ID No.: UN1993  
Proper Shipping Name: Flammable Liquids, n.o.s., (Naphtha (petroleum), heavy alkylate, Terpenes Hydrocarbon)  
Hazard Class: 3  
Packing Group: III

IATA and IMDG

UN/ID No.: UN1993  
Proper Shipping Name: Flammable Liquids, n.o.s., (Naphtha (petroleum), heavy alkylate, Terpenes Hydrocarbon)  
Hazard Class: 3  
Packing Group: III  
Marine Pollutant (IMDG Code): Not listed (49 CFR 172.101).  
Transportation in bulk (IMDG - Annex II of MARPOL 73/78 and IBC Code): Not offered in bulk for transport overseas.

#### SECTION 15. REGULATORY INFORMATION

---

TSCA: All components of this product are on the TSCA inventory or are exempt from TSCA inventory requirements under 40 CFR 720.30.

SARA Section 302: The components of this product are either not regulated or regulated, but present in negligible concentrations.

SARA TITLE III Section 311/312:

Immediate (Acute) Health	Yes	Fire Hazard	Yes
Delayed (Chronic) Health	Yes	Reactive Hazard	No

SARA Title 313: This material contains the following chemical components with known CAS numbers subject to reporting requirements (40 CFR 372): 2-(2-butoxyethoxy)ethanol CAS# 112-34-5, % by wt. = 13%.

CERCLA: This product does not have a reportable quantity.

United States Right-To-Know: (Naphtha (petroleum), heavy alkylate) CAS #64741-65-7 – Massachusetts, Pennsylvania and New Jersey.

Proposition 65: This material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

RCRA: A waste containing this product may have the RCRA hazardous waste no. D001 (Ignitable) (40 CFR 261.22).

**SECTION 16.**

**OTHER INFORMATION**

Date Prepared: August 10, 2015

Hazard Ratings (HMIS): Health 2, Flammability 2, Reactivity 1 (Scale 0 – 4). Personal Protection Rating to be supplied by user based on use conditions.

Product VOC: 45%

Carefully read all instructions on label before handling this product.

Keep out of reach of children.

“FOR INDUSTRIAL USE ONLY”

<b>Abbreviation</b>	<b>Full Name/Explanation</b>
ACGIH	American Conference of Government Industrial Hygienists
CAS	Chemical Abstract Service
CERCLA	Comprehensive Environmental Response Compensation and Liability Act
CNS	Central Nervous System
CFR	Code of Federal Regulations
DOT	Department of Transportation
EC	Effective Concentration
HMIS	Hazardous Material Information System
LC	Lethal Concentration
LD	Lethal Dose
NA	Not Applicable
ND	Not Determined
NE	Not Established
NIOSH	National Institute for Occupational Safety and Health
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
RCRA	Resource Conservation Recovery Act
SARA	Superfund Amendments and Reauthorization Act
STEL	Short-Term Exposure Limit
TLV	Threshold Limit Value
TSCA	Toxic Substance Control Act
VOC	Volatile Organic Compounds

The information contained herein is based on data available to us and is believed to be correct. We make no warranty, however, expressed or implied regarding the accuracy of these data or the results obtained from the use thereof.

Regulatory Standards: DOT TITLE 49, Code of Federal Regulations 172.101: Parts 100 to 177, Revised 10/1/92.

SUPER FUND AMENDMENTS REAUTHORIZATION ACT OF 1986, TITLE III TOXIC SUBSTANCE CONTROL ACT LIST (TSCA)- INGREDIENTS LISTED. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES NATIONAL TOXICOLOGICAL PROGRAM (NTP) REPORT OF CARCINOGENS INTERNATIONAL AGENCY FOR RESEARCH ON CANCER (IARC) MONOGRAPHS, OCCUPATIONAL SAFETY & HEALTH REGULATIONS. CODE OF FED. REGS. FOOD & DRUG, 21 PARTS 170 to 199, Revised 4/1/91, 173.310.